



# **Product Info**

Brand: POLYLINE® UPC: 85339992981 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 2 lbs Carton Length: 6 in Carton Width: 8 in Carton Height: 10 in Country of Origin: United States of America Color: Gray (RAL 7035) with clear cover

Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AMP864CC

8"x6"x4" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off clear cover Availability: For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com Enclosure Type: JIC Size Cover Type: Clear Polycarbonate Closure Type: 4-Screw Lift-Off Mounting Description: Nonmetal feet fastened to back side brass inserts Box Features: Installation Type:

Height: 7.94 in

Width: 6.16 in

**Depth:** 3.98 in

Usable Depth: 4.18 in Volume: 237 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13;  $\underline{File}$  No.  $\underline{E120175}$ 

#### Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters) 2. RoHS directive





