



## Product Info

**Brand:** AM Series

**Carton Quantity:** 1

**Carton Weight:** 1.134 kg

**Country of Origin:** India

**Color:** Gray (RAL 7035)

**Material:** Fiberglass Reinforced Polyester - compression molded SMC box and cover

## AM1084I

AM Series, IEC certified, fiberglass wall mount enclosure with 4-screw lift-off cover. External Hardware are of SS 304, IP Rating - IP 66.

**Enclosure Type:** JIC Size

**Cover Type:** Opaque

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Height:** 299 mm

**Width:** 249 mm

**Depth:** 115 mm

## Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

## Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

IEC-62208 , IEC-60695-2-11:2000, IEC-60529:2013-08, IEC-60068-2-2:2007, IEC-62262-2002, UL-94 5VA, RoHS Compliant



## Fire Classification:

Glow Wire at 960°C