



AMP1082

10"x8"x2" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off cover

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size **Cover Type:** Opaque

Closure Type: 4-Screw Lift-Off

Mounting Description: Nonmetal feet fastened to back

side brass inserts

Height: 9.93 in **Width:** 8.15 in **Depth:** 2.7 in

Usable Depth: 2.68 in Volume: 290 cu in

Product Info

Brand: POLYLINE®
UPC: 85339973904
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 3 lbs
Carton Length: 6 in
Carton Width: 10 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Carton Height: 12 in

Patents: U.S. Patent No. 7,572,975 **Material:** Polycarbonate box and cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)

2. RoHS directive





WARNING – PROP 65 Click here for more information!