



## 1099-AB Single gang fiberglass adjustable electrical box for use with nonmetallic sheathed cable.

**Carton Quantity:** 50

**Carton Weight:** 29

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Adjustable box (SLIDERBOX®)

**Installation Type:** New Work

**Height:** 3.83 in

**Width:** 3.375 in

**Depth:** 3.563 in

**Volume:** 22.5 cu in

**Number of Gangs:** 1

### Product Info

**Brand:** SLIDERBOX

**UPC:** 85339988387

**Carton Weight:** 29 lbs

**Carton Length:** 21 in

**Carton Width:** 9 in

**Carton Height:** 12.5 in

**Country of Origin:** United States of America

**Patents:** Patent Pending

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners

### Features:

- fiberglassBOX® material, so no putty pad is needed when following the Uniform Building Code (3" minimum distance between boxes).
- Sound rated up to STC (Sound Transmission Class) rating of 54
- 0"-2" of adjustability to fit most wall finishes and arrives preset for 1/2" standard drywall applications.
- 6-32 UNC tapped holes for easy device mounting
- Corrosion resistant metal bracket for a solid hold to a wood or metal wall stud.
- One screw design for easy adjustability.
- Knockout for a 1/2" NM connector

### Application:

New work residential construction 2 HR fire resistive walls

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

### Fire Classification:

#### Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

**Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 3 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---