



ALLIED
MOULDED
PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506



9335-NKFR

3.5" dia. round fan support box for use with nonmetallic sheathed cable *Replacement for 9335-NFR*

Carton Quantity: 50

Mounting Description: Nail-on with fether ring nails

Box Type: Ceiling - Fan/Fixture

Box Features: Nails, Speed "K" nonmetallic clamps

Installation Type: New Work

Width: 3-1/2 in

Depth: 2-7/8 in

Volume: 20.5 cu in

Fan Rating: 35lbs

Fixture Rating: 50lbs

Product Info

Brand: fiberglassBOX

UPC: 85339412021

UNSPSC: 39121316

Carton Weight: 26 lbs

Carton Length: 20 in

Carton Width: 12 in

Carton Height: 16 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl chloride clamps

Box Diameter: 3.5

Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: [File No. E30594](#)



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
