



## 9335-NKFR

3.5" dia. round fan support box for use with nonmetallic sheathed cable *Replacement for 9335-NFR* 

**Carton Quantity: 50** 

Mounting Description: Nail-on with fetter ring nails

Box Type: Ceiling - Fan/Fixture

Box Features: Nails, Speed "K" nonmetallic clamps

**Installation Type:** New Work

Width: 3-1/2 in

Depth: 2-7/8 in

Volume: 20.5 cu in

Fan Rating: 35lbs

Fixture Rating: 50lbs

# **Product Info**

Brand: fiberglassBOX UPC: 85339412021 UNSPSC: 39121316 Carton Weight: 26 lbs Carton Length: 20 in Carton Width: 12 in

Carton Height: 16 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl

chloride clamps

Box Diameter: 3.5

#### Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

#### **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support), UL approved for back-to-back installation

**Box Diameter:** 3.5

Standards:

ANSI / UL 514C: File No. E30594



### Fire Classification:

**Fire Test of Building Construction Materials** 

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)