



## 9338-ESK

3.5" dia. round fixture support (15 lbs.) box for use with

nonmetallic sheathed cable **Carton Quantity:** 50

Mounting Description: Snap bracket/metal ears wall

compression

Box Type: Wall - Fixture Support

Box Features: Metal ears, Snap bracket, Speed "K"

nonmetallic clamps

**Installation Type:** Old Work

Width: 3-1/2 in
Depth: 2 in
Volume: 14 cu in
Fixture Rating: 15lbs

## **Product Info**

**Brand:** fiberglassBOX **UPC:** 85339460060

UNSPSC: 39121308 Carton Weight: 21 lbs

Carton Length: 19 in Carton Width: 9 in Carton Height: 12 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

**Box Diameter: 3.5** 

#### Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

#### **Application:**

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)