



# 9305-GK

3.5" dia. round fixture support box for use with nonmetallic sheathed cable *Replacement for 9305-G* 

**Carton Quantity: 50** 

Mounting Description: Bottom mount button holes or

flange holes

Box Type: Ceiling - Fixture

Box Features: Grounding strap, Speed "K" nonmetallic

clamps

**Installation Type:** Old Work

Width: 3-1/2 in

Depth: 1-3/4 in

Volume: 14 cu in

Fixture Rating: 50lbs

# **Product Info**

Brand: fiberglassBOX
UPC: 85339100362
UNSPSC: 39121316
Carton Weight: 17 lbs
Carton Length: 21 in
Carton Width: 10 in

Country of Origin: United States of America

Color: Off white

Carton Height: 11 in

Material: Fiberglass reinforced polyester

**Additional Materials:** Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground

screw, Polyvinyl chloride clamps

Box Diameter: 3.5

#### Features:

Machine tapped fixture holes, ground strap, round exterior for easy cut-in, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

#### **Application:**

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support – flange mount) and ceilings (50 lbs. fixture support – bottom mounted)

ibs. fixture support – bottom mount

**Box Diameter:** 3.5

**Standards:** 

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

#### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)