



9305-GK

3.5" dia. round fixture support box for use with nonmetallic sheathed cable *Replacement for 9305-G*

Carton Quantity: 50

Mounting Description: Bottom mount button holes or

flange holes

Box Type: Ceiling - Fixture

Box Features: Grounding strap, Speed "K" nonmetallic

clamps

Installation Type: Old Work

Width: 3-1/2 in

Depth: 1-3/4 in

Volume: 14 cu in

Fixture Rating: 50lbs

Product Info

Brand: fiberglassBOX
UPC: 85339100362
UNSPSC: 39121316
Carton Weight: 17 lbs
Carton Length: 21 in
Carton Width: 10 in

Country of Origin: United States of America

Color: Off white

Carton Height: 11 in

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground

screw, Polyvinyl chloride clamps

Box Diameter: 3.5

Features:

Machine tapped fixture holes, ground strap, round exterior for easy cut-in, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support – flange mount) and ceilings (50 lbs fixture support – bettom mounted)

lbs. fixture support - bottom mounted)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)