



9305-SK

3.5" dia. round fixture support box for use with nonmetallic sheathed cable Replacement for 9305-S

Carton Quantity: 50

Mounting Description: Bottom mount button holes or

flange holes

Box Type: Wall - Fixture Support

Box Features: Snap bracket, Speed "K" nonmetallic

clamps

Installation Type: Old Work

Width: 3-1/2 in **Depth:** 1-3/4 in Volume: 14 cu in Fixture Rating: 15lbs

Product Info

Brand: fiberglassBOX **UPC:** 85339273516 **UNSPSC: 39121308** Carton Weight: 22 lbs Carton Length: 21 in

Carton Width: 10 in Carton Height: 11 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

Box Diameter: 3.5

Features:

Machine tapped fixture holes, round exterior for easy cutin, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures,

Speed "K" Clamps factory installed

Application:

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-**Hours or less**

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)