



9355-SGK

3.5" dia. round fixture support box for use with

nonmetallic sheathed cable **Carton Quantity:** 48

Mounting Description: Snap bracket/box flange wall

compression

Box Type: Wall - Fixture Support

Box Features: Grounding strap, Snap bracket, Speed "K"

nonmetallic clamps

Installation Type: Old Work

Width: 3-1/2 in Depth: 2-3/4 in Volume: 22 cu in Fixture Rating: 15lbs

Product Info

Brand: fiberglassBOX UPC: 85339681519 UNSPSC: 39121308 Carton Weight: 26 lbs Carton Length: 20 in

Carton Width: 17 in Carton Height: 11 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

Box Diameter: 3.5

Features:

Machine tapped fixture holes, ground strap, round exterior for easy cut-in, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)