



## **PC213-BH**

3.5" dia. round fixture support box for use with

nonmetallic sheathed cable **Carton Quantity:** 24

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

**Box Type:** Ceiling - Fixture **Box Features:** Bar hanger **Installation Type:** New Work

Width: 3-1/2 in
Depth: 2-13/16 in
Volume: 21 cu in
Fixture Rating: 50lbs

# **Product Info**

Brand: flexBOX UPC: 85339980308 UNSPSC: 39121316 Carton Weight: 27 lbs Carton Length: 17 in

Carton Width: 15 in Carton Height: 11 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners **Box Diameter:** 3.5

#### Features:

Molded-in splined device holes

## **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)