



## Product Info

**Brand:** flexBOX

**UPC:** 85339980124

**UNSPSC:** 39121316

**Carton Weight:** 13 lbs

**Carton Length:** 19 in

**Carton Width:** 11 in

**Carton Height:** 16 in

**Country of Origin:** United States of America

**Color:** Black

**Patents:** U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Carbon steel fasteners, Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

**Box Diameter:** 3.5

## PC213-NG

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

**Carton Quantity:** 50

**Mounting Description:** Nail-on with fether ring nails

**Box Type:** Ceiling - Fixture

**Box Features:** Grounding strap, Nails

**Installation Type:** New Work

**Width:** 3-1/2 in

**Depth:** 2-13/16 in

**Volume:** 21 cu in

**Fixture Rating:** 50lbs

### Features:

Molded-in splined device holes, ground strap

### Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

**Box Diameter:** 3.5

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**WARNING** - PROP 65  
[Click here for more information!](#)

### Fire Classification:

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*