



PC2230W

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Carton Quantity: 24

Mounting Description: Snap bracket/box flange wall compression

Box Type: Wall - Fixture Support

Box Features: Snap bracket

Installation Type: Old Work

Width: 3-1/2 in

Depth: 2-13/16 in

Volume: 21.5 cu in

Product Info

Brand: flexBOX

UPC: 85339980285

UNSPSC: 39121316

Carton Weight: 9 lbs

Carton Length: 13 in

Carton Width: 9 in

Carton Height: 13 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Galvanized steel brackets and plated carbon steel fasteners

Box Diameter: 3.5

Features:

Machine tapped fixture holes, round exterior for easy cut-in

Application:

Old work residential construction 2 HR fire resistive walls. Meets requirements of Articles 314.27 (A1) and 314.27 (D) of the 2014 NEC. Suitable for use in mounting utilization equipment (wall sconce lights, alarm system strobe/speaker, smoke detector and low-profile LED lighting) weighing six pounds or less.

Box Diameter: 3.5

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

⚠ WARNING - PROP 65
[Click here for more information!](#)

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling

Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
