



## **PC2230W**

3.5" dia. round fixture support box for use with

nonmetallic sheathed cable **Carton Quantity:** 24

Mounting Description: Snap bracket/box flange wall

compression

**Box Type:** Wall - Fixture Support **Box Features:** Snap bracket

**Installation Type:** Old Work

Width: 3-1/2 in Depth: 2-13/16 in Volume: 21.5 cu in

## **Product Info**

**Brand:** flexBOX **UPC:** 85339980285

UNSPSC: 39121316 Carton Weight: 9 lbs Carton Length: 13 in

Carton Width: 9 in Carton Height: 13 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners **Box Diameter:** 3.5

#### **Features:**

Machine tapped fixture holes, round exterior for easy cut-

### **Application:**

Old work residential construction 2 HR fire resistive walls. Meets requirements of Articles 314.27 (A1) and 314.27 (D) of the 2014 NEC. Suitable for use in mounting utilization equipment (wall sconce lights, alarm system strobe/speaker, smoke detector and low-profile LED lighting) weighing six pounds or less.

Box Diameter: 3.5

Standards:

ANSI / UL 514C: File No. E30594



### Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)