



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



Product Info

Brand: SLIDERBOX

UPC: 85339945062

UNSPSC: 39121316

Carton Weight: 10 lbs

Carton Length: 13 in

Carton Width: 9 in

Carton Height: 8 in

Country of Origin: United States of America

Color: Beige

Patents: U.S. Patent No. 7,855,338, U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners, Galvanized steel brackets and plated carbon steel fasteners, Plated carbon steel fasteners

Box Diameter: 4

SB-CBFR

4" dia. round adjustable fan support box for use with nonmetallic sheathed cable

Carton Quantity: 12

Mounting Description: 3 Screws

Box Type: Ceiling - Fan/Fixture

Box Features: Adjustable box (SLIDERBOX®), Screws

Installation Type: New Work, Old Work

Width: 4 in

Depth: 2-3/4 in

Volume: 25 cu in

Fan Rating: 70lbs

Fixture Rating: 90lbs

Features:

Machine tapped fixture holes and bolts/nuts for fan mounting, adjustable mounting plate for additional substrate thickness

Application:

New and old work residential construction 2 HR fire resistive floors and ceilings (70 lbs. fan support and 90 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)
