

#### 419-636-4217 222 N. Union St. Bryan, OH 43506



# SB-CBFR

4" dia. round adjustable fan support box for use with nonmetallic sheathed cable **Carton Quantity:** 12 **Mounting Description:** 3 Screws **Box Type:** Ceiling - Fan/Fixture **Box Features:** Adjustable box (SLIDERBOX®), Screws **Installation Type:** New Work, Old Work **Width:** 4 in **Depth:** 2-3/4 in **Volume:** 25 cu in **Fan Rating:** 70lbs **Fixture Rating:** 90lbs

# **Product Info**

Brand: SLIDERBOX UPC: 85339945062 UNSPSC: 39121316 Carton Weight: 10 lbs Carton Length: 13 in Carton Width: 9 in Carton Height: 8 in Country of Origin: United States of America Color: Beige

Patents: U.S. Patent No. 7,855,338, U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners, Galvanized steel brackets and plated carbon steel fasteners, Plated carbon steel fasteners

Box Diameter: 4

# Features:

Machine tapped fixture holes and bolts/nuts for fan mounting, adjustable mounting plate for additional substrate thickness

### Application:

New and old work residential construction 2 HR fire resistive floors and ceilings (70 lbs. fan support and 90 lbs. fixture support)

### Box Diameter: 4 Standards:

#### Standards:

ANSI / UL 514C: File No. E30594



# Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: <u>File No. CEYY.R9379</u> (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)