



SB-CB

4" dia. round adjustable fixture support box for use with

nonmetallic sheathed cable

Carton Quantity: 12

Mounting Description: 2 Screws

Box Type: Ceiling - Fixture

Box Features: Adjustable box (SLIDERBOX®), Screws

Installation Type: New Work, Old Work

Width: 4 in Depth: 2-3/4 in Volume: 25 cu in Fixture Rating: 50lbs

Product Info

Brand: SLIDERBOX UPC: 85339945055 UNSPSC: 39121316 Carton Weight: 3 lbs Carton Length: 13 in

Carton Width: 12 in Carton Height: 5 in

Country of Origin: United States of America

Color: Beige

Patents: U.S. Patent No. 7,855,338, U.S. Patent No.

6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners, Galvanized

steel brackets and plated carbon steel fasteners

Box Diameter: 4

Features:

Machine tapped fixture holes, adjustable mounting plate for additional substrate thickness

Application:

New and old work residential construction 2 HR fire resistive floors and ceilings (50 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)