



**ALLIED  
MOULDED  
PRODUCTS, Inc.**

**419-636-4217  
222 N. Union St.  
Bryan, OH 43506**



## Product Info

**Brand:** SLIDERBOX

**UPC:** 85339945055

**UNSPSC:** 39121316

**Carton Weight:** 3 lbs

**Carton Length:** 13 in

**Carton Width:** 12 in

**Carton Height:** 5 in

**Country of Origin:** United States of America

**Color:** Beige

**Patents:** U.S. Patent No. 7,855,338, U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Carbon steel fasteners, Galvanized steel brackets and plated carbon steel fasteners

**Box Diameter:** 4

## SB-CB

4" dia. round adjustable fixture support box for use with nonmetallic sheathed cable

**Carton Quantity:** 12

**Mounting Description:** 2 Screws

**Box Type:** Ceiling - Fixture

**Box Features:** Adjustable box (SLIDERBOX®), Screws

**Installation Type:** New Work, Old Work

**Width:** 4 in

**Depth:** 2-3/4 in

**Volume:** 25 cu in

**Fixture Rating:** 50lbs

### Features:

Machine tapped fixture holes, adjustable mounting plate for additional substrate thickness

### Application:

New and old work residential construction 2 HR fire resistive floors and ceilings (50 lbs. fixture support)

**Box Diameter:** 4

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**⚠ WARNING - PROP 65**  
[Click here for more information!](#)

### Fire Classification:

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---