



## SB-CBG

4" dia. round adjustable fixture support box for use with nonmetallic sheathed cable

**Carton Quantity:** 12

**Mounting Description:** 2 Screws

**Box Type:** Ceiling - Fixture

**Box Features:** Adjustable box (SLIDERBOX®), Grounding strap, Screws

**Installation Type:** New Work, Old Work

**Width:** 4 in

**Depth:** 2-3/4 in

**Volume:** 25 cu in

**Fixture Rating:** 50lbs

## Product Info

**Brand:** SLIDERBOX

**UPC:** 85339945079

**UNSPSC:** 39121316

**Carton Weight:** 4 lbs

**Carton Length:** 13 in

**Carton Width:** 9 in

**Carton Height:** 7 in

**Country of Origin:** United States of America

**Color:** Beige

**Patents:** U.S. Patent No. 7,855,338, U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Carbon steel fasteners, Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw, Galvanized steel brackets and plated carbon steel fasteners

**Box Diameter:** 4

## Features:

Machine tapped fixture holes, adjustable mounting plate for additional substrate thickness

## Application:

New and old work residential construction 2 HR fire resistive floors and ceilings (50 lbs. fixture support)

**Box Diameter:** 4

## Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**⚠ WARNING - PROP 65**  
[Click here for more information!](#)

## Fire Classification:

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---