



## **9350-FANB**

4" dia. round fan support box for use with nonmetallic

sheathed cable

**Carton Quantity: 20** 

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

Box Type: Ceiling - Fan/Fixture

Box Features: Bar hanger

Installation Type: New Work

Width: 4 in Depth: 2-7/16 in

Volume: 22.5 cu in Fan Rating: 35lbs

Fixture Rating: 50lbs

# **Product Info**

**Brand:** fiberglassBOX **UPC:** 85339990215

UNSPSC: 39121316

Carton Weight: 44 lbs

Carton Length: 16 in Carton Width: 15 in

Carton Height: 11 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

**Box Diameter:** 4

#### Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed. New bar design – Replaces P/N 9350-FRBKB

#### **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture

support)

**Box Diameter: 4** 

Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)