



## **9350-FANVB**

4" dia. round fan support box for use with nonmetallic sheathed cable

**Carton Quantity: 18** 

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

Box Type: Ceiling - Fan/Fixture

Box Features: Air-sealed flange (energy efficient), Bar

hanger, Grounding strap

**Installation Type:** New Work

Width: 4 in
Depth: 2-7/16 in
Volume: 22.5 cu in
Fan Rating: 35lbs
Fixture Rating: 50lbs

## **Product Info**

Brand: Vapor Seal
UPC: 85339990222
UNSPSC: 39121316
Carton Weight: 31 lbs
Carton Length: 18 in
Carton Width: 16 in

Carton Height: 12 in

Country of Origin: United States of America

Color: Off white

**Patents:** U.S. Patent No. 6,908,003 B2 **Material:** Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyurethane flange, Polyvinyl

chloride clamps

**Box Diameter: 4** 

#### Features:

Polyurethane flange for single drywall offset, machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed. New fan bar design – Replaces P/N 9350-FRBKBV

#### **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support) – air-sealed electrical fan support box for Energy Star homes

**Box Diameter:** 4

Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 – Energy Efficient Air-Sealed Boxes for Electrical Applications



### **Fire Classification:**

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)