



# **Product Info**

Brand: fiberglassBOX UPC: 85339704249 UNSPSC: 39121316 Carton Weight: 48 lbs Carton Length: 26 in

Carton Width: 16 in Carton Height: 18 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated

carbon steel fasteners, Plated carbon steel fasteners,

Polyvinyl chloride clamps

**Box Diameter: 4** 

## 9364-FRBKOW

4" dia. round fan support box for use with nonmetallic sheathed cable

**Carton Quantity: 20** 

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

**Box Type:** Ceiling - Fan/Fixture **Box Features:** Bar hanger

Installation Type: Old Work

Width: 4 in
Depth: 1-11/16 in
Volume: 15 cu in
Fan Rating: 35lbs
Fixture Rating: 50lbs

#### Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed, individual point-of-purchase carton.

### **Application:**

Old work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support)

**Box Diameter:** 4

**Standards:** 

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)