



## 9369-FB

4" dia. round fan support box for use with nonmetallic

sheathed cable

**Carton Quantity: 25** 

Mounting Description: Bottom mount

**Box Type:** Ceiling - Fan/Fixture **Installation Type:** New Work

Width: 4 in Depth: 1-3/4 in Volume: 16 cu in Fan Rating: 35lbs

Fixture Rating: 50lbs

# **Product Info**

Brand: fiberglassBOX UPC: 85339765004 UNSPSC: 39121316 Carton Weight: 12 lbs Carton Length: 15 in

Carton Width: 11 in Carton Height: 8 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Plated carbon steel fasteners,

Polyvinyl chloride clamps

**Box Diameter:** 4

#### Features:

Fixture support bolts and nuts included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps

factory installed

### **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support)

**Box Diameter: 4** 

Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)