



## 9370-FR

4" dia. round fan support box for use with nonmetallic

sheathed cable

**Carton Quantity: 24** 

Mounting Description: Bottom mount

Box Type: Ceiling - Fan/Fixture

Installation Type: New Work, Old Work

Width: 4 in
Depth: 1-1/2 in
Volume: 8 cu in
Fan Rating: 70lbs
Fixture Rating: 110lbs

# **Product Info**

Brand: fiberglassBOX
UPC: 85339766001
UNSPSC: 39121316
Carton Weight: 6 lbs
Carton Length: 16 in
Carton Width: 9 in

Country of Origin: United States of America

Color: Off white

Carton Height: 5 in

Material: Fiberglass reinforced polyester

Additional Materials: Nonmetallic pop-in cable clamp,

Plated carbon steel fasteners

**Box Diameter:** 4

#### **Features:**

1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting

#### **Application:**

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support)

Box Diameter: 4
Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive