



Product Info

Brand: fiberglassBOX

UPC: 85339766001

UNSPSC: 39121316

Carton Weight: 6 lbs

Carton Length: 16 in

Carton Width: 9 in

Carton Height: 5 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Nonmetallic pop-in cable clamp,
Plated carbon steel fasteners

Box Diameter: 4

9370-FR

4" dia. round fan support box for use with nonmetallic sheathed cable

Carton Quantity: 24

Mounting Description: Bottom mount

Box Type: Ceiling - Fan/Fixture

Installation Type: New Work, Old Work

Width: 4 in

Depth: 1-1/2 in

Volume: 8 cu in

Fan Rating: 70lbs

Fixture Rating: 110lbs

Features:

1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting

Application:

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
