





PC234-N

4" dia. round fixture support box for use with nonmetallic sheathed cable Carton Quantity: 50 Mounting Description: Nail-on with fetter ring nails Box Type: Ceiling - Fixture Box Features: Nails Installation Type: New Work Width: 4 in Depth: 2-5/16 in Volume: 23 cu in Fixture Rating: 50lbs

Product Info

Brand: flexBOX
UPC: 85339980254
UNSPSC: 39121316
Carton Weight: 12 lbs
Carton Length: 22 in
Carton Width: 12 in
Carton Height: 14 in
Country of Origin: United States of America
Color: Black
Patents: U.S. Patent No. 6,365,831 B1
Material: Polycarbonate
Additional Materials: Carbon steel fasteners
Box Diameter: 4

Features:

Molded-in splined device holes

Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: <u>File No. CEYY.R9379</u> (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less Distance between boxes in adjacent cavities may be

reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)