419-636-4217
222 N. Union St.
Bryan, OH 43506

# PC234-NG

4" dia. round fixture support box for use with nonmetallic sheathed cable

**Carton Quantity:** 50

**Mounting Description:** Nail-on with fetter ring nails

**Box Type:** Ceiling - Fixture

**Box Features:** Grounding strap, Nails

**Installation Type:** New Work

**Width:** 4 in

**Depth:** 2-5/16 in

**Volume:** 23 cu in

**Fixture Rating:** 50lbs

## Product Info

**Brand:** flexBOX

**UPC:** 85339980261

**UNSPSC:** 39121316

**Carton Weight:** 13 lbs

**Carton Length:** 22 in

**Carton Width:** 12 in

**Carton Height:** 13 in

**Country of Origin:** United States of America

**Color:** Black

**Patents:** U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Carbon steel fasteners, Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

**Box Diameter:** 4

**Features:**

Molded-in splined device holes, ground strap

**Application:**

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

**Box Diameter:** 4

**Standards:**

ANSI / UL 514C: File No. E30594

LISTED

**WARNING** – PROP 65
Click here for more information!

**Fire Classification:**

**Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

**Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less**

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*