



# PC234-NG

4" dia. round fixture support box for use with nonmetallic

sheathed cable

**Carton Quantity: 50** 

Mounting Description: Nail-on with fetter ring nails

Box Type: Ceiling - Fixture

Box Features: Grounding strap, Nails

Installation Type: New Work

Width: 4 in Depth: 2-5/16 in Volume: 23 cu in Fixture Rating: 50lbs

## **Product Info**

Brand: flexBOX UPC: 85339980261 UNSPSC: 39121316 Carton Weight: 13 lbs Carton Length: 22 in

Carton Width: 12 in Carton Height: 13 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

**Additional Materials:** Carbon steel fasteners, Galvanized ground strap with plated carbon steel fastener and green

plated carbon steel ground screw

**Box Diameter: 4** 

#### Features:

Molded-in splined device holes, ground strap

### **Application:**

New work residential construction 2 HR fire resistive walls

and ceilings (50 lbs. fixture support)

**Box Diameter:** 4

Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)