



## AC9500BULK

4" dia. round fixture support box with 7" square mounting flange for use with nonmetallic sheathed cable

Carton Quantity: 50

Mounting Description: Back side mount with fasteners

**Installation Type:** New Work

Width: 4 in

Depth: 1-1/4 in

Volume: 12 cu in

Fixture Rating: 15lbs

# **Product Info**

**UPC:** 85339095033 **UNSPSC:** 39121309 **Carton Weight:** 29 lbs **Carton Length:** 22 in

Carton Height: 10 in

Carton Width: 20 in

Country of Origin: United States of America

Color: Beige

Material: Fiberglass reinforced polyester

Additional Materials: Nonmetallic pop-in cable clamp

**Box Diameter:** 4

#### **Features:**

Machine tapped fixture holes, "pop-in" cable clamp, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

#### **Application:**

Residential home – exterior light fixture electrical box (15 lb fixture rating) for use with nonmetallic sheathed cable

**Box Diameter:** 4

Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be  $4-\frac{1}{2}$  feet from one another

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)