



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



9342-C2

4 square inch electrical junction box for use with nonmetallic sheathed cable

Carton Quantity: 50

Mounting Description: Bottom mount

Box Type: Wall - Junction

Box Features: Wire clamps

Installation Type: New Work

Height: 4 in

Width: 4 in

Depth: 2-1/4 in

Volume: 27.3 cu in

Product Info

Brand: fiberglassBOX

UPC: 85339103462

UNSPSC: 39121332

Carton Weight: 25 lbs

Carton Length: 21 in

Carton Width: 9 in

Carton Height: 13 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Plated carbon steel clamp and fasteners

Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED



WARNING - PROP 65

[Click here for more information!](#)

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive

*directory and Allied Moulded's CEYY.9379 (Outlet boxes
and fittings classified for fire resistance)*
