



## 9342-C2

4 square inch electrical junction box for use with

nonmetallic sheathed cable **Carton Quantity:** 50

**Mounting Description:** Bottom mount

**Box Type:** Wall - Junction **Box Features:** Wire clamps **Installation Type:** New Work

Height: 4 in Width: 4 in Depth: 2-1/4 in Volume: 27.3 cu in

# **Product Info**

Brand: fiberglassBOX UPC: 85339103462 UNSPSC: 39121332 Carton Weight: 25 lbs Carton Length: 21 in

Carton Width: 9 in Carton Height: 13 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Plated

carbon steel clamp and fasteners

#### Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

### Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications – 2 HR fire resistive walls

#### Standards:

ANSI / UL 514C: File No. E30594



### Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)