



# **PJ-32H**

4 square inch electrical junction box for use with

nonmetallic sheathed cable **Carton Quantity:** 48

Mounting Description: Stud mount hanger bracket

offset for flush mount plaster ring

Box Type: Wall - Junction
Box Features: "HL" hanger
Installation Type: New Work

Height: 4 in Width: 4 in Depth: 2-1/2 in Volume: 32.5 cu in

## **Product Info**

Brand: flexBOX UPC: 85339990024 UNSPSC: 39121332 Carton Weight: 17 lbs Carton Length: 20 in

Carton Width: 10 in Carton Height: 21 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polyvinyl Chloride

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Plated carbon steel fasteners

#### Features:

Machine tapped cover screw holes, cover screws included

### **Application:**

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device

applications - 2 HR fire resistive walls

#### Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)