



## 9318

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 100

**Carton Weight:** 28

**Mounting Description:** Surface mount

**Box Type:** Wall - Switch/Receptacle

**Installation Type:** New Work, Old Work

**Height:** 4-3/16 in

**Width:** 2-1/4 in

**Depth:** 2 in

**Number of Gangs:** 1

## Product Info

**Brand:** fiberglassBOX

**UPC:** 9318

**UNSPSC:** 39121308

**Carton Weight:** 28 lbs

**Carton Length:** 19 in

**Carton Width:** 13 in

**Carton Height:** 11 in

**Country of Origin:** United States of America

**Color:** Off white

## Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

## Application:

Surface mounted box with side and bottom Romex cable openings

## Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**WARNING** - PROP 65

[Click here for more information!](#)

## Fire Classification:

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be

reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---