



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



Product Info

Brand: fiberglassBOX

UPC: 9318

UNSPSC: 39121308

Carton Weight: 28 lbs

Carton Length: 19 in

Carton Width: 13 in

Carton Height: 11 in

Country of Origin: United States of America

Color: Off white

9318

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 100

Carton Weight: 28

Mounting Description: Surface mount

Box Type: Wall - Switch/Receptacle

Installation Type: New Work, Old Work

Height: 4-3/16 in

Width: 2-1/4 in

Depth: 2 in

Number of Gangs: 1

Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

Surface mounted box with side and bottom Romex cable openings

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)
