ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506

9318

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 100
Carton Weight: 28
Mounting Description: Surface mount
Box Type: Wall - Switch/Receptacle
Installation Type: New Work, Old Work
Height: 4-3/16 in
Width: 2-1/4 in
Depth: 2 in
Number of Gangs: 1

Product Info

Brand: fiberglassBOX
UPC: 9318
UNSPSC: 39121308
Carton Weight: 28 lbs
Carton Length: 19 in
Carton Width: 13 in
Carton Height: 11 in
Country of Origin: United States of America
Color: Off white

Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

Surface mounted box with side and bottom Romex cable openings

Standards:

ANSI / UL 514C: File No. E30594

UL LISTED

WARNING – PROP 65
Click here for more information!

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling

Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)