



# 9318

Single gang electrical box for use with nonmetallic

sheathed cable

Carton Quantity: 100 Carton Weight: 28

Mounting Description: Surface mount Box Type: Wall - Switch/Receptacle Installation Type: New Work, Old Work

Height: 4-3/16 in Width: 2-1/4 in Depth: 2 in

Number of Gangs: 1

# **Product Info**

**Brand:** fiberglassBOX

**UPC:** 9318

UNSPSC: 39121308 Carton Weight: 28 lbs Carton Length: 19 in Carton Width: 13 in

Carton Height: 11 in

Country of Origin: United States of America

Color: Off white

#### **Features:**

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

### **Application:**

Surface mounted box with side and bottom Romex cable openings

# Standards:

ANSI / UL 514C: File No. E30594



### **Fire Classification:**

### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes

and fittings classified for fire resistance)