



### 9368-EK

Single gang electrical box for use with nonmetallic

sheathed cable

Carton Quantity: 100

**Mounting Description:** Metal ears **Box Type:** Wall - Switch/Receptacle

Box Features: Metal ears, Speed "K" nonmetallic clamps

Installation Type: Old Work

Height: 3-1/4 in Width: 2-3/8 in Depth: 3-3/16 in Volume: 18.0 cu in Number of Gangs: 1

## **Product Info**

Brand: fiberglassBOX UPC: 85339760030 UNSPSC: 39121308 Carton Weight: 32 lbs

Carton Length: 21 in Carton Width: 13 in Carton Height: 14 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps

#### Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

# Application:

Old work residential construction 2 HR fire resistive walls and ceilings

#### Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

## Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive