



## **AM1084HP9**

10"x8"x4" AM Series fiberglass wall mount enclosure assembly with 2-screw hinged cover and 9 (30.5mm) pushbutton holes

## Availability:

Made to order; For up-to-date delivery on this product,

please contact us at 1-800-722-2679 or

sales@alliedmoulded.com

**Enclosure Type:** Pushbutton **Cover Type:** Opaque

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Closure Type: 2-Screw

Height: 10.14 in Width: 8.26 in Depth: 4 in

**Usable Depth:** 3.68 in **Volume:** 346 cu in

# **Product Info**

Brand: AM Series UPC: 85339840329 UNSPSC: 39121326 Carton Quantity: 1 Carton Weight: 5 lbs Carton Length: 5 in

Carton Height: 13 in

Carton Width: 11 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

 $\textbf{Material:} \ \, \textbf{ULTRAGUARD} \, \textbf{\textit{Fiberglass reinforced polyester-}}$ 

compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Brass inserts, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place

gasket system

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Designed to protect push-button switches from damage and wear, these enclosures have holes for mounting push buttons and an internal compartment to house associated wires and mechanisms. Push buttons are often used for operating industrial machines or processes for indoor and outdoor applications. Note: 22.5mm hole designs are available by adding a "22" to the part number (i.e. AM1084HP922).

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

## Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive





WARNING - PROP 65
Click here for more information!