ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506

AM1086RW

10"x8"x6" AM-R Series fiberglass wall mount enclosure assembly with raised 4-screw lift-off window cover

Availability:
Made to order; For up-to-date delivery on this product, please contact us at 866-283-9324 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 4-Screw Lift-Off

Mounting Description: Stainless steel feet fastened to back side brass inserts

Height: 10.14 in

Width: 8.26 in

Depth: 6.01 in

Usable Depth: 7.12 in

Volume: 513 cu in

Product Info

Brand: AM-R Series

UPC: 85339911289

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 7 lbs

Carton Length: 9 in

Carton Width: 11 in

Carton Height: 13 in

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear window

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Brass inserts, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:
1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive

WARNING – PROP 65
Click here for more information!