



## Product Info

**Brand:** AM Series  
**UPC:** 8533997490  
**UNSPSC:** 39121324  
**Carton Quantity:** 1  
**Carton Weight:** 7 lbs  
**Carton Length:** 6 in  
**Carton Width:** 15 in  
**Carton Height:** 15 in  
**Country of Origin:** United States of America  
**Color:** Gray (RAL 7035) with clear window

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AM1224W

12"x12"x4" AM Series fiberglass wall mount enclosure assembly with 4-screw lift-off window cover

### Availability:

**Made to order:** For up-to-date delivery on this product, please contact us at 866-283-9324 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Enclosure Type:** JIC Size

**Cover Type:** Opaque with Viewing Window

**Closure Type:** 4-Screw Lift-Off

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

### Box Features:

#### Installation Type:

**Height:** 12.14 in

**Width:** 12.14 in

**Depth:** 4.13 in

**Usable Depth:** 3.62 in

**Volume:** 609 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



**WARNING - PROP 65**  
[Click here for more information!](#)