



ALLIED
MOULDED
PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506



Product Info

Brand: AM Series

UPC: 85339975069

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 8 lbs

Carton Length: 8 in

Carton Width: 15 in

Carton Height: 15 in

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear window

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AM1226W

12"x12"x6" AM Series fiberglass wall mount enclosure assembly with 4-screw lift-off window cover

Availability:

Made to order: For up-to-date delivery on this product, please contact us at 866-283-9324 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 4-Screw Lift-Off

Mounting Description: Stainless steel feet fastened to back side brass inserts

Box Features:

Installation Type:

Height: 12.14 in

Width: 12.14 in

Depth: 6.13 in

Usable Depth: 5.62 in

Volume: 903 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



WARNING - PROP 65
[Click here for more information!](#)