



### **Product Info**

Brand: AM-R Series UPC: 85339919032 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 18 lbs Carton Length: 11 in Carton Width: 21 in

Carton Height: 23 in

**Country of Origin:** United States of America **Color:** Gray (RAL 7035) with clear window

**Material:** ULTRAGUARD® Fiberglass reinforced polyester compression molded SMC box and cover with bonded clear polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

# **AM1868RHW**

18"x16"x8" AM-R Series fiberglass wall mount enclosure assembly with raised 2-screw hinged window cover

Availability:

**Made to order**; For up-to-date delivery on this product, please contact us at 1-800-722-2679 or

sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 2-Screw

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features: Installation Type:

**Height:** 18.4 in **Width:** 16.4 in **Depth:** 8.01 in

**Usable Depth:** 9.11 in **Volume:** 2453 cu in

## Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

#### **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive





