



# **Product Info**

Brand: AM Series
UPC: 85339920847
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 18 lbs
Carton Length: 9 in

Carton Width: 21 in Carton Height: 25 in

**Country of Origin:** United States of America **Color:** Gray (RAL 7035) with clear window

**Material:** ULTRAGUARD® Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear

polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

### **AM2068HW**

20"x16"x8" AM Series fiberglass wall mount enclosure assembly with 2-screw hinged window cover

Availability:

**Made to order**; For up-to-date delivery on this product, please contact us at 1-800-722-2679 or

sales@alliedmoulded.com
Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 2-Screw

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features: Installation Type:

Height: 20 in Width: 16 in Depth: 8.01 in

Usable Depth: 7.58 in Volume: 2602 cu in

## **Features:**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

#### Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





