



## AM2068ILW

AM Series, IEC certified, fiberglass wall mount enclosure with Snap Latch Locking System & One Side Hinge with 6mm PC Clear Window. External Hardware are of SS 304, IP Rating - IP 66.

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Height:** 550 mm

**Width:** 447 mm

**Depth:** 165 mm

**Volume:** 2602 cu mm

## Product Info

**Brand:** AM Series

**Carton Quantity:** 1

**Country of Origin:** India

**Color:** Gray (RAL 7035) with clear window

**Material:** Fiberglass Reinforced Polyester - compression molded SMC box and cover

**Additional Materials:** 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware, 304 stainless steel external hardware (hinges/latches/fasteners), Brass inserts

## Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

## Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Fire Classification:

Glow Wire at 960°C