+91.80.67926666
NO.199 & 242, Road No. 8
Bommasandra, Jigani Link Road
Bangalore, Karnataka



AM2068ILW

AM Series, IEC certified, fiberglass wall mount enclosure with Snap Latch Locking System & One Side Hinge with 6mm PC Clear Window. External Hardware are of SS 304, IP Rating - IP 66.

Mounting Description: Stainless steel feet fastened to back side brass inserts

Height: 550 mm

Width: 447 mm

Depth: 165 mm

Volume: 2602 cu mm

Product Info

Brand: AM Series

Carton Quantity: 1

Country of Origin: India

Color: Gray (RAL 7035) with clear window

Material: Fiberglass Reinforced Polyester - compression molded SMC box and cover

Additional Materials: 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware, 304 stainless steel external hardware (hinges/latches/fasteners), Brass inserts

Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Fire Classification:

Glow Wire at 960◦C