



Product Info

Brand: AM-R Series
UPC: 85339921011
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 20 lbs
Carton Length: 11 in
Carton Width: 21 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Carton Height: 25 in

Material: ULTRAGUARD® Fiberglass reinforced polyester -

compression molded SMC box and Cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket

system

AM2068R

20"x16"x8" AM-R Series fiberglass wall mount enclosure assembly with raised 4-screw lift-off cover

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size
Cover Type: Opaque

Closure Type: 4-Screw Lift-Off

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features:
Installation Type:
Height: 20 in
Width: 16 in
Depth: 8.01 in
Usable Depth: 9.21 in
Volume: 2602 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; $\underline{\text{File No. }}$ $\underline{\text{E120175}}$

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





WARNING - PROP 65
Click here for more information!