



# **AM24240RLW**

24"x24"x10" Control Series fiberglass wall mount enclosure assembly with raised hinged window cover and stainless-steel snap latches

## **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

**Enclosure Type:** Wall Cabinets

Cover Type: Opaque with Viewing Window

Closure Type: Metal Snap Latch

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Height: 24 in Width: 24 in Depth: 10 in

**Usable Depth:** 10.54 in

Volume: 6843 cu in

# **Product Info**

Brand: Control Series
UPC: 85339924340
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 29 lbs
Carton Length: 13 in
Carton Width: 29 in

**Carton Height:** 29 in **Country of Origin:** United States of America

**Color:** Gray (RAL 7035) with clear window

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear \\ \end{tabular}$ 

polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Brass inserts, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive







Click here for more information!