



## AM363016L3PT

36"x30"x16" Empire Series fiberglass wall mount enclosure assembly with hinged cover and stainless-steel 3-point latching handle

### Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Enclosure Type:** Wall Cabinets

**Cover Type:** Opaque

**Closure Type:** 3-Point Handle

**Mounting Description:** Molded flange

**Height:** 36.04 in

**Width:** 30.04 in

**Depth:** 14.16 in

**Usable Depth:** 14.27 in

**Volume:** 16976 cu in

## Product Info

**Brand:** Empire Series

**UPC:** 85339994817

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 65 lbs

**Carton Length:** 15 in

**Carton Width:** 35 in

**Carton Height:** 45 in

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external 3-point latching handle, 316 stainless steel external hardware (hinges/latches/fasteners), EPDM Spring loaded gasket, Plated alloy steel bonding fastener, Plated carbon steel internal hardware

## Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a spring loaded gasket system.

## Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 4, and 4X; [File No. E120175](#)

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



**WARNING - PROP 65**

[Click here for more information!](#)

---