



## AM664

6"x6"x4" AM Series fiberglass wall mount enclosure assembly with 4-screw lift-off cover

### Availability:

For up-to-date delivery on this product, please contact us at 866-283-9324 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Enclosure Type:** JIC Size

**Cover Type:** Opaque

**Closure Type:** 4-Screw Lift-Off

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Box Features:**

**Installation Type:**

**Height:** 6.1 in

**Width:** 6.1 in

**Depth:** 4.05 in

**Usable Depth:** 3.76 in

**Volume:** 156 cu in

## Product Info

**Brand:** AM Series

**UPC:** 85339906643

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 3 lbs

**Carton Length:** 6 in

**Carton Width:** 9 in

**Carton Height:** 10 in

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; [File No. E120175](#)

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)
2. RoHS directive



**WARNING** - PROP 65  
[Click here for more information!](#)